

AFS FITTINGS

AFS METAL CLAMPS



Metal clamps are produced specifically for all kinds of flexible air duct connections. They consist of stainless steel strip and locking devices.

Strip steel bands are produced 9 mm wide and 0.6 mm thick from AISI 430 quality stainless steel strip. Strip steel band edges are rounded to prevent damage while connecting flexible air ducts. Strip steel bands are packed in 30m lengths in a plastic dispenser.

The locking devices provide easy and fast clamping. The screw head is specially shaped so that simple tools like a screwdriver or spanner can be used. Housings are nickel plated and screws are zinc plated.

The strip steel banding and clip system is easily cut and installed, making it the fastest fixing system available. The band is cut, folded through the slot on the clamp, and taking care of the direction of the dimples on the strip, installed around the duct.

PROPERTIES & ADVANTAGES

STAINLESS STEEL STRIP

AISI 430 quality stainless steel
Non-flammable
Inseparable
Highly corrosion resistant
Chemically resistant
Maintenance free

LOCKING DEVICES

Non-flammable
Nickel plated housing
Zinc plated screw
Fast and simple installation
Chemically resistant
Low installation cost

STRIP STEEL CONSTRUCTION

Easy to store
Easy to transport
Easy to install
Low installation cost

TECHNICAL PROPERTIES

	STRIP STEEL BANDING SYSTEM & LOCKING DEVICES
Clamp Construction	AISI 430 stainless steel
Locking Device Construction	Nickel plated housing, zinc plated screw
Clamp Thickness	600 micron
Clamp Width	9 mm
Standard length (Clamp)	30 m
Packing (Clamp)	Single plastic cassette
Standard Quantity(Locking devices)	50 pieces

